

SilentX 450W Power Supply Unit

The Shuttle XPC Accessory PC55 provides the additional power for Shuttle compatible Shuttle XPCs needed to satisfy the demands of high power graphics cards and large capacity storage devices. It is the optimal solution for power users wanting to upgrade without compromising the stability, low-noise, and portability of the XPC.

XPC Accessory **PC55**



Feature Highlight	
Input	<ul style="list-style-type: none"> Input Voltage: 90~264V AC Input Current: 7A / 3.5A (100/240V AC) Frequency: 63Hz / 47 Hz Efficiency: > 75% at full load Active PFC (Power Factor Correction)
Output	<ul style="list-style-type: none"> Total combined output (3.3V / 5V / 12V): 450W Hold up time: >16ms (full load, 115V AC) Rise time: <20ms (full load, nominal line) Short circuit protection (SCP): latch off other protection: OVP, OCP Power good signal: TTL compatible
Environmental	<ul style="list-style-type: none"> Operating Temperature: 10~50°C Storage Temperature: -40~70°C MTBF: > 100.000 hours (75% load, 25°C) Noise: <34dB
Safety/EMI	<ul style="list-style-type: none"> Safety: UL, CUL, TÜV, CB, BSMI EMI: FCC, CE, BSMI
Connectors	<ul style="list-style-type: none"> Mainboard 8 pin + 6 pin 1x PCI-Express power for graphics 3x S-ATA, 2x Molex Cable length designed for the XPC
Other	<ul style="list-style-type: none"> Dimension: 150 x 86 x 83 mm (l x w x h) Smart Fan Temp-Speed controlXPC
Compatibility	<ul style="list-style-type: none"> Compatible with the following Shuttle XPCs: SB81P, SB95P, SB95PV2, SD31P, SD37P2, SD39P2, SN25P, SN26P, SN27P2



**Mainboard
8 pin**



**Mainboard
6 pin**



**PCI-
Express
6 pin**



**2x
Molex**



**3x
S-ATA**



Article number: **PC55**

Order number: **PCZ-PC55**

UPC-Barcode:



8 11686 00514 8